

Brake Cleaner

Propellant propane butane + Co2 - non aggressive to plastics, EPS



PRODUCT DESCRIPTION

Brake Cleaner is a highly active special cleaning agent with intensive cleaning effect for oily and greasy machine parts, disc brakes and brake parts, such as brake choke, plates and clutch linings.

APPLICATIONS

Ideal as a cleaning agent for industry and trade, for repairs and assembly

DIRECTION FOR USE

Spray at a distance of approximately 20 cm onto the contaminated surface and allow to drain. Let parts air-dry or clean with a dry cloth. In case of heavy soiling, repeat application several times

TECHNICAL SPECIFICATIONS

Application Temperature	+5°C to +25°C
Base	Hydrocarbon solvents
Density	0.690
Frost Resistance	Up to -15°C
Pressure at 20°C [bar]	5.5
Pressure at 50°C [bar]	7.5
Extrusion rate [g/s]	6.2

These are typical values

PACKAGING DESCRIPTION

Can

SHELF LIFE

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

