



Den Braven

Cleaner

Removes cured silicone residue



PRODUCT DESCRIPTION

Zwaluw Sili-Kill® was specifically developed to remove cured silicone residue.

KEY BENEFITS

- Removes hardened silicone residues

APPLICATIONS

Cleaner was developed for de-greasing and cleaning of substrates from glass, plastics, metals, powder coated aluminium and ceramics. Removing traces of grease and mild surface contaminants. De-greasing and cleaning of paint systems, which can influence adhesion of the sealant.

DIRECTION FOR USE

Cut the silicone sealant and remove as much as possible with a sharp knife. Shake Den Braven Sili-Kill® well before use. Apply excessive amounts of Zwaluw Sili-Kill® to the cured silicone residue. After 20-30 minutes the sealant silicone residue can easily be removed with a putty knife or a wooden spatula for vulnerable substrates. If necessary repeat the treatment. Afterwards wash with water and soap and let dry.

TECHNICAL SPECIFICATIONS

Application Temperature	+5°C to +40°C
Density	0,72 g/ml
Frost Resistance	Up to -15°C

These are typical values

SURFACE PREPARATIONS AND FINISHING

Before using the Zwaluw Sili-Kill® refer to the Health & Safety Sheet. Contact Den Braven for a full recommendation. Clean hands with Zwaluw Handclean.

PACKAGING DESCRIPTION

- Can

For product specifications, please refer to the Product Detail Page

COLOUR

Transparent

SHELF LIFE

In unopened original packaging kept between +5°C and +25°C, shelf life is up to 24 months from production date, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

