

Concentrated Finisher

Concentrated joint sealant finishing additive



PRODUCT DESCRIPTION

Zwaluw Finisher is a neutral universal additive for the tooling of sealants in joints. Zwaluw Finisher is more than 90% Biodegradable.

KEY BENEFITS

- Optimal results
- Fast finishing

APPLICATIONS

Finisher was developed for wet tooling of sealants in joints.

DIRECTION FOR USE

Dilute the Finisher to a 1 to 3% solution in water (1 to 3 parts of Finisher to 100 parts of water). After application of the sealant the joint surface and the neighbouring surfaces must be moistened with diluted Finisher by using a brush or spray. Now the joint can be tooled with a spatula or a putty knife. Once smooth the joint can be finished using a finger dipped in diluted Finisher.

TECHNICAL SPECIFICATIONS

Application Temperature	+5°C to +40°C	
Density	1,03 g/ml	
Frost Resistance	Up to -15°C	
pH-value	pH = 7,0 - 7,5 pH not diluted 8,0 - 8,5	

These are typical values

PACKAGING DESCRIPTION

```
- Flacor
- Can
```

For product specifications, please refer to the Product Detail Page

COLOUR

Transparent

SHELF LIFE

Store between +5°C and +25°C and in a cool, dry place. Shelf life is 24 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

