



Den Braven

Contact Spray

Contact spray to displace moisture



PRODUCT DESCRIPTION

Contact Spray is a multi-purpose product. It is used for maintaining and servicing electric installations in motor vehicles. A single treatment with Contact Spray is sufficient in most cases and saves a lot of time!

KEY BENEFITS

- Removes leakage currents and voltage loss
- Keeps contacts, fuses and cable connections free of oxidation and sulphide layers
- New and gives protection from ultraviolet radiation

APPLICATIONS

For servicing and maintaining electrical systems in the automotive sector. This versatile contact spray can be used for many applications. Displaces moisture and protects against rust and corrosion. Eliminates leakage currents and voltage loss. Prevents oxidation and sulphide deposits on contacts, fuses and cable connections. Facilitates current flow. Dissolves resin (do not spray onto coils and similar connections).

DIRECTION FOR USE

Vigorously shake can. Spray generously onto surfaces and briefly allow to react. Remove any excess with a cloth. Repeat to remove stubborn deposits. Spray onto entire ignition system and distributor cap when vehicle engine fails to start.

TECHNICAL SPECIFICATIONS

| | |
|-------------------------------|--------------|
| Base | Hydrocarbons |
| Density | 0.692 |
| Frost Resistance | Up to -15°C |
| Pressure at 20°C [bar] | 4.2 |
| Pressure at 50°C [bar] | 7.7 |
| Extrusion rate [g/s] | 1.6 |

These are typical values

LIMITATIONS

- Do not spray onto coils and similar connections

SHELF LIFE

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

