



Den Braven

# Foliefix® SPUR

Membrane adhesive



## PRODUCT DESCRIPTION

Zwaluw Foliefix® SPUR is a hybrid based adhesive for bonding plastic foils and vapour barriers in the building industry. The product is free of isocyanates, silicones and solvents. After application the adhesive cures with atmospheric moisture to form a durable pressure sensitive rubber mass.

## KEY BENEFITS

- Instant grab
- Isocyanate and silicone free
- Flexible

## APPLICATIONS

Zwaluw Foliefix® SPUR was designed for adhesion of plastic foils like PE, PVC, EPDM, DPC, aluminium foil, carton, Kraft paper and non-woven to stone, concrete, plaster, metal and wood. Zwaluw Foliefix® SPUR reaches optimal adhesion in 2 to 3 days at room temperature.

## DIRECTION FOR USE

For a complete overview see our website or contact Den Braven.

## TECHNICAL SPECIFICATIONS

Application Temperature		+5°C to +35°C
Base		Hybrid
Density	ISO 1183-1	1.22 g/ml
Temperature Resistance		-40°C to +80°C

These are typical values

## LIMITATIONS

- Nicht geeignet für PP, PC, PMMA, PTFE, weiche Kunststoffe, Neopren

## SURFACE PREPARATIONS AND FINISHING

All substrates must be clean, dry and free of dust, grease and other loose material. Adhesion tests prior to the application are recommended. Clean the substrates thoroughly by using Zwaluw Cleaner. Apply Zwaluw Foliefix® SPUR with a professional caulking gun.

## CLEANING

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

## PACKAGING DESCRIPTION

- Cartridge
- For product specifications, please refer to the Product Detail Page

## COLOUR

- Green

## SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life up to 12 months from production date, stored in a dry place.

## CERTIFICATIONS

- A+ (Eurofins ISO 16000)

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

## WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

## DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held

liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

