

# **PU-Rooffix**

# Roof adhesive based on liquid polyurethane



# PRODUCT DESCRIPTION

Zwaluw PU-Rooffix is a liquid polyurethane roof adhesive for bonding insulation panels onto concrete and galvanised steel. The adhesive cures by reacting with moisture on the substrate and environmental humidity and forms a strong, durable, water resistant connection. The adhesive fills gaps completely, by slightly foaming during curing, depending on the amount of moisture on the substrate.

# **KEY BENEFITS**

- Slightly foams during curing
- Water resistant after curing
- Usage 20-30 g/m2

# **APPLICATIONS**

Zwaluw PU-Rooffix was developed for bonding of PS, PU, glass fibre and rock wool panels to concrete, galvanised and coated steel

# **DIRECTION FOR USE**

Do not use below +5°C. Although the adhesive will expand and fill larger cavities, there is a risk that a surface-skin will already be formed before the adhesive makes contact with the insulation panel. No adhesion will be achieved on these areas. Keep the adhesive containers out of direct sunlight to prevent the adhesive becoming too liquid because of the heat. Prevent any deformation for 24 hours after bonding. For more information see Technical Bulletins in the Knowledge Base on

our website www.denbraven.com.

#### **TECHNICAL SPECIFICATIONS**

Application Temperature		+5°C to +30°C
Base		Polyurethane
Density	ISO 1183-1	1,12 g/ml
Frost Resistance		Up to -15°C
Open Time	@ +23°C/50% RH	15 minutes

These are typical values

# **LIMITATIONS**

Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

#### **SURFACE PREPARATIONS AND FINISHING**

Application temperature (applies to environment and substrates): +5°C to +30°C. All substrates must be solid, clean, dry, and free from grease and dust. Remove loose particles from surfaces. Always test adhesion prior to application. For proper curing one of the substrates must be porous.

# **CLEANING**

Uncured material and tools can be cleaned by using Zwaluw Universal PU-Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

# PACKAGING DESCRIPTION

For product specifications, please refer to the Product Detail Page

# SHELF LIFE

If kept stored in a cool, dry place, in unopened original packaging, between +5°C and +25°C, shelf life is up to 6 months from production date.

# **HEALTH & SAFETY**

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

# **WARRANTY & GUARANTEE**

Bostik warrants that its product complies, within its shelf life, to its specification.

# **DISCLAIMER**

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an

PU-Rooffix – 2025, 20 August

indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

