



Den Braven

# Profstop Universal

Paintable putty based on linseed oil



## PRODUCT DESCRIPTION

Zwaluw Profstop Universal is a high quality paintable putty based on linseed oil, synthetic resins and fillers.

## KEY BENEFITS

- Suitable for wooden, steel and concrete window frames
- Paintable

## APPLICATIONS

Zwaluw Profstop Universal was developed for sealing and pointing of single sheets of glass up to 0,6m<sup>2</sup> in wooden, steel and concrete window frames.

Note: curing time can vary from several months to a year. For applications that must be quickly painted over, we recommend Zwaluw Monustop.

## DIRECTION FOR USE

Secure the glass with sprigs, clips or cleats. The minimum joint dimension of the Zwaluw Profstop Universal is 10x10 mm. The maximum joint dimension of the Zwaluw Profstop Universal is 25x25 mm.

## TECHNICAL SPECIFICATIONS

<b>Application Temperature</b>	+5°C to +30°C
<b>Density</b>	2,1 g/ml
<b>Frost Resistance</b>	Up to -15°C
<b>Skin Formation</b>	2-4 months
<b>Consistency</b>	Paste

These are typical values

## LIMITATIONS

- Not suitable for insulation or laminated glass

## SURFACE PREPARATIONS AND FINISHING

Application temperature: +5°C to +30°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Zwaluw Profstop Universal adheres perfectly without the use of primer to most non porous substrates. Porous substrates must be pre-treated with Zwaluw Primer Universal. Always test adhesion prior to application. Use Zwaluw Finisher to smooth the joint. Rebates should be pre-treated twice with an undercoat for optimal adhesion.

## PAINTABILITY

Zwaluw Profstop Universal is perfectly paintable with most paint systems after sufficient skin formation. Skin formation and curing times are dependant on the conditions. Note: skin formation time can be up from several months to one year. For applications that must be quickly painted over, we recommend Zwaluw Monustop and if it is not painted over the Zwaluw Silstop®.

## CLEANING

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

## PACKAGING DESCRIPTION

- Bucket
- Jar

For product specifications, please refer to the Product Detail Page

## COLOUR

Natural

## SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life up to 12 months from production date, stored in a dry place.

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

## WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

## DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part

of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

