



Den Braven

# Rust Primer Red Brown

Alkyd-resin-based, fast-drying



## PRODUCT DESCRIPTION

Zwaluw Rust Primer Red is a fast drying corrosion protection primer. It has excellent rust protection abilities.

## DIRECTION FOR USE

All surfaces must be dry, clean and free of dirt or corrosion. Surfaces should have room-temperature, if possible. Shake can vigorously for approx. 3 min as soon as the mixing balls are audible. Apply cross-wise in several coats with a distance of approx. 15-20 cm.

## TECHNICAL SPECIFICATIONS

<b>Application Temperature</b>	+16°C to +25°C
<b>Base</b>	Alkyd-resin
<b>Curing Time</b>	24 hours
<b>Density</b>	0.824
<b>Frost Resistance</b>	Up to -15°C
<b>Tack free time</b>	35-40 minutes
<b>Pressure at 20°C [bar]</b>	3.7
<b>Pressure at 50°C [bar]</b>	7.3
<b>Extrusion rate [g/s]</b>	1.5
<b>Temperature range [°C]</b>	-25°C to +80°C
<b>Dust free after [min]</b>	70

These are typical values

## SURFACE PREPARATIONS AND FINISHING

Surfaces must be clean, dry and free of grease, rust and loose particles.

## PAINTABILITY

Paintable with most lacquers and paints, test prior to application.

## SHELF LIFE

Store between +5°C and +25°C in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

## WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

## DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

