



Den Braven

# Spray Adhesive

Multi-purpose adhesive for porous and non-porous substrates



## PRODUCT DESCRIPTION

Spray Adhesive can be used for all minor adhesive problems in motor vehicle technology, trade, modeling, DIY, hobby and household.

## KEY BENEFITS

- Instant adhesive strength
- Adjustable nozzle

## APPLICATIONS

Spray Adhesive is suitable for paper, cardboard, wood, thin veneer, cork, leather, textiles, polystyrene foam, rubber, plastic foil (except PVC/PE).

## DIRECTION FOR USE

Shake intensively before application. The surfaces to be bonded must be free of grease and dust and have to be roughened (grinding dust must be removed!). For absorbent substrates (wood, felt, etc.), the application rate should be increased. Spraying distance about 20-25 cm. For contact bonding, adhesive has to be applied separately on both parts. Depending on ambient temperature and layer thickness, the adhesive has to dry for 5 to 15 minutes. Then the parts are put together and pressed. A subsequent correction is hardly possible. For assembly bonding the two parts are also provided separately with adhesive. After a short flash-off time the parts are put together with adhesive still moist. Corrections are here, depending on the material properties, for an even longer time possible. The bond should remain unloaded until the adhesive has fully bonded (about 24 hours). To avoid a possible blockage of the nozzle, turn the can

- after use and spray until no more adhesive leaks the nozzle. Note: The suitability of the adhesive, in conjunction with the various substrates has to be clarified by preliminary tests.

## TECHNICAL SPECIFICATIONS

<b>Application Temperature</b>	+5°C to +35°C
<b>Base</b>	Adhesive solution based on synthetic rubber and resin in a hydrocarbon/ketone solvent blend
<b>Curing Time</b>	Adhesive becomes tacky in 1 to 3 minutes and should be bonded within 10 to 20 minutes. Adhesive remains 'wet' for 15 to 25 minutes.
<b>Temperature Resistance</b>	-25°C to +45°C
<b>Temperature range [°C]</b>	-25°C to +45°C

These are typical values

## PACKAGING DESCRIPTION

Can

## SHELF LIFE

Store between +5°C and +25°C in shaded conditions. Shelf life is 12 months when stored as recommended in original unopened packaging.

## HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

## WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

## DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in

accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



**HOTLINE**

Smart help +31 162 491 000