



Den Braven

White Grease

White grease containing lithium grease



PRODUCT DESCRIPTION

White Grease Spray creates long-lasting lubrication and protection. It can be applied as grease lubrication on highly-stressed bearings, spindles and guides in machines. However, it can also be applied as a long-lasting lubricant. It prolongs the intervals after which lubrication becomes necessary owing to its double lubricating effect. It ensures longer functioning of expensive installations with fewer failures and repairs.

KEY BENEFITS

- Pure white
- Long-term resistance to salt water
- Temperature resistant from -30°C up to +120°C (only for a short period of time)

APPLICATIONS

White Grease Spray is suitable for lubricating highly-stressed slide, roller and swing bearings as well as spindles and guides in machines used in industry, vehicle construction and shipbuilding as well as in operating building and agricultural machinery. Lubricates moveable parts and sliding surfaces. Is suitable as a back-up lubricating grease on spotless lubricating points. Reduces the wear and tear on bearings, shafts, chains, chain wheels, brake hinges and locks. It is also suitable as a battery pole grease, a parting agent and preservative.

DIRECTION FOR USE

Thoroughly clean the lubricating points (e.g. with Brake Cleaner) and remove old grease residues. Shake the aerosol vigorously (for about 2 minutes) before use until the metal ball can be heard clearly. Spray sparingly and evenly from a distance of approx. 20cm. After use, turn the aerosol upside down and empty it by spraying its contents until there is only propellant left.

TECHNICAL SPECIFICATIONS

Base	Lithium grease
Density	0.665
Frost Resistance	Up to -15°C
Pressure at 20°C [bar]	4.0
Pressure at 50°C [bar]	7.1
Extrusion rate [g/s]	1.6

These are typical values

PACKAGING DESCRIPTION

Can

SHELF LIFE

Storage between +5°C and +25°C and in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use. These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.

