



Den Braven

Houtreparatiemassa

2 - component epoxy resin based paste



PRODUCT DESCRIPTION

Zwaluw Houtreparatiemassa is a 2-component lightweight repair compound for wood. After curing the product can be processed like wood.

KEY BENEFITS

- Good flow resistance
- Fast curing
- Sandable and paintable
- Almost no shrinkage

APPLICATIONS

Zwaluw Houtreparatiemassa was developed for repairing defects in rotten wood, both in construction of new and existing wood. Also suitable for substrates like stone and metal. Zwaluw Houtreparatiemassa has almost no shrinkage and is weather resistant.

DIRECTION FOR USE

Mix both components in equal volume parts to a homogeneous mixture with a single colour. The potlife of the product is 15 minutes after mixing at +20°C.
After approx. 5 hours at +20°C the product can be sanded and painted. Preferably wait 24 hours to paint.

TECHNICAL SPECIFICATIONS

Application Temperature		+10°C to +30°C
Frost Resistance		Up to -15°C
Open Time	@ +23°C/50% RH	15 minutes
Shrinkage		<2%
Mixing Ratio		1:1
Paintable	@ +23°C/50% RH	after 5 hours
Sandable	@ +23°C/50% RH	after 5 hours

These are typical values

LIMITATIONS

- Not suitable for PE, PP, PC, PMMA, PTFE, soft plastics, neoprene and bituminous substrates

SURFACE PREPARATIONS AND FINISHING

Application temperature +10°C to +30°C (applies to environment and substrates). All substrates must be solid, clean, dry, and free of grease and dust. Clean substrates with Zwaluw Cleaner. Always test adhesion prior to application.

PAINTABILITY

Zwaluw Houtreparatiemassa is paintable with most paint systems. We recommend testing compatibility with paint prior to application.

CLEANING

Uncured material and tools can be cleaned by using Zwaluw Cleaner. Cured material can only be mechanically removed. Hands can be cleaned with Zwaluw Wipes.

PACKAGING DESCRIPTION

- Can
- For product specifications, please refer to the Product Detail Page

COLOUR

Natural

SHELF LIFE

In unopened original packaging between +5°C and +25°C, shelf life is up to 24 months from date of production, stored in a dry place.

HEALTH & SAFETY

Product Safety Data Sheet must be read and understood before use.
These are available on request and via our websites

WARRANTY & GUARANTEE

Bostik warrants that its product complies, within its shelf life, to its specification.

DISCLAIMER

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public or used in any other way without Bostik written consent. The technical information in this document serves as an indication and is non-exhaustive. Bostik is not liable for any damage, either directly or indirectly, due to (editorial) errors, incompleteness and/or incorrectness of this document. This includes, but is not limited to, incompleteness and/or incorrectness due to technological changes or any research conducted between the date of publication of this document and the date on which the product is acquired. Bostik reserves the right to amend the wording of this document. Bostik cannot be held liable for any damage, either directly or indirectly, due to the use of the product(s) depicted in this document. The user must read and understand the information in this document and other documents relating to the products prior to the use of the product. The user is responsible for performing all the requisite tests to make sure that the product is suitable for its intended use. We have no influence in what way the product is applied and/or any circumstances relating to events occurring during storage or transport and therefore we do not accept any liability for damage whatsoever. All deliveries are made exclusively in accordance with our general terms of conditions which have been filed at the Dutch Chamber of Commerce.



HOTLINE

Smart help +31 162 491 000